

HUSTLER® COMMERCIAL ZERO-TURN MOWER

SUPER S™

A STAND-ON WITH EXCEPTIONAL
OPERATOR COMFORT, CONTROL
AND MANEUVERABILITY



THE COMPACT CHOICE FOR PROFESSIONALS

Hustler's Super S™ features superior operator comfort and positioning, operator-friendly controls and a compact stance that makes navigating tight spaces easy. It's the perfect choice for highly landscaped properties or any landscape where maneuverability is a top priority. Its smaller footprint also allows for more mowers to fit on a trailer and more space for storage.



SMOOTHTRAK™ STEERING
Responsive, precise steering control.



OPERATOR COMFORT
Features exceptional operator positioning for all-day comfort.



COMPACT STANCE
Perfect for tight spaces and for trailering from job-to-job.



OR



Find A Hustler Dealer
visit www.hustlerturf.com

ENGINE

Manufacturer	Kawasaki FS541, FX600, FX691, FX730, FX850 Kohler ECV730 EFI, ECV740 EFI
HP	36"deck: 15HP - FS541 36"deck: 19HP - FX600 48/52"deck: 22HP - FX691 60"deck: 23.5HP - FX730 52" deck: 27HP - FX850 60" deck: 27HP - FX850 52"deck: 23HP - ECV730 EFI 60"deck: 25HP - ECV740 EFI (Per SAE J 1995)
Displacement	603-747cc
Cooling	Air cooled
Air Cleaner	Heavy duty air canister (not standard on 36" deck)
Engine Warranty	3 year

DRIVE SYSTEM

Type	Dual hydrostatic
Pumps	36": Hydro-Gear 10cc 48, 52, 60": Hydro-Gear 12cc
Wheel Motors	36": Parker TL0195 48, 52, 60": Parker TL0240
Speed	36": Up to 8 mph 48, 52, 60": Up to 9 mph
Parking Brakes	Hand operated

DECKS

Cutting Width	Side discharge: 36", 48", 52", 60"
Cutting Heights	1.5" - 5.5"
Deck Lift	Hand operated
Depth	5.5"
Blades	36": 2 48", 52", 60": 3
Blade Length	36" deck: 17.86" x 2.50" x .20" 48" deck: 16.50" x 2.50" x .20" 52" deck: 17.86" x 2.50" x .20" 60" deck: 20.50" x 2.50" x .20"
Spindles	Ductile cast iron with steel shafts and sealed ball bearings
Deck Belts	1
Drive	Electric PTO clutch
Construction	36": 7 ga. Fabricated 48, 52, 60": 10 ga. Fabricated
Spindle Mounts	36": 7 ga. with 11 ga. doubler 48, 52, 60": 10 ga. with 7 ga. doubler
Impact/Trim Areas	11 ga. formed channel with rolled bottom

* Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning and terrain.

** Specifications are subject to change without notice.

CONSTRUCTION

Frame	36": 1.5" x 2" x .188" steel 48, 52, 60": 1.5" x 3" x .188" steel
Engine Plate	7 ga. with 11 ga. jackshaft doubler
Front Caster Wheels	Mounted tapered wheel bearings and debris cap
Front Caster Forks	Fabricated 3/8" steel
Operator Platform	7 ga. with embossed tread pattern

GENERAL

Fuel Capacity	36": 6.5 gallons 48, 52, 60": 7.3 gallons
Front Tire	36": 11 x 4 - 5 smooth 48", 52", 60": 13 x 5 - 6 smooth
Drive Tire	36": 18 x 8.5 - 10 48", 52": 20 x 10 - 10 60": 20 x 12 - 10

DIMENSIONS

Weight	36": 871 lbs 48": 995 lbs 52": 1055 lbs 60": 1065 lbs
Height	47.8"
Length	36": 63.5" 48", 52": 64" 60": 66.5"
Width w/ chute up	36": 39" 48": 50.4" 52": 54.4" 60": 62.4"
Tire Width	36": 36.3" 48", 52": 44.7" 60": 49.1"

PRODUCTIVITY*

Acres Per Hour	36": 2.33 48": 3.49 52": 3.79 60": 4.36
----------------	--

OPTIONAL ACCESSORIES

Mulch kit
Mesh side bagger (3 bushels)
Metal side bagger (3.5 bushels)
Light kit
Cup holder
Trash basket
Stripe kit

SUPER S | AT A GLANCE

- 36", 48", 52" or 60" welded steel side-discharge deck
- Heavy-duty fabricated frame – unmatched durability
- Exclusive SmoothTrak™ steering – responsive, precise control
- Operator-friendly, ergonomic controls
- Powerful engine options
- Compact stance – great for tight spaces
- Superior operator comfort and positioning
- Up to 8 or 9 mph speed options (depending on deck size)
- 6.5 or 7.3 gallon fuel capacity (depending on deck size)



Visit hustlerturf.com
and try our compare products tool!