

HUSTLER® COMMERCIAL ZERO-TURN MOWER

# SUPER Z®

## FEATURES HUSTLER'S VX4® DECK, HEAVY-DUTY HYDRAULICS



### A COMBO OF RELIABILITY AND PRODUCTIVITY THAT TRULY IS SUPER

The Super Z® stands apart with Hustler's acclaimed VX4® deck technology proven to cut and disperse grass more quickly and efficiently regardless of conditions. It continues with hydraulics unmatched by the competition. Plus, enjoy the comforts of a high-back seat with armrests. At up to 14 miles per hour and an 11.7 gallon fuel tank, you'll enjoy the incredible productivity of the Super Z.



#### HEAVY-DUTY PERFORMANCE

Three engine options, large fuel capacity and up to 14 mph top speed.



#### LEGENDARY VX4® DECK

Engineered for a 'perfect' cut every time.



#### SUPERIOR PRODUCTIVITY

Heavy-duty hydraulics deliver more power, torque than many other machines.



LIMITED  
**LIFETIME WARRANTY**  
FRAME & LEADING EDGE OF DECK

LIMITED  
WARRANTY

**2** YEAR  
NO  
HOUR LIMIT

OR

LIMITED  
WARRANTY

**5** YEAR  
**500**  
HOUR

Find A Hustler Dealer  
visit [www.hustlerturf.com](http://www.hustlerturf.com)

## ENGINE

Manufacturer	Kawasaki FX850V, FX1000V Kohler 824EFI
HP	54", 60" deck: 27HP - FX850 60", 66", 72" deck: 35HP - FX1000 60" deck: 33HP - Kohler 824 EFI 66", 72" deck: 33HP - Kohler 824 EFI (Per SAE J1995)
Displacement	FX850: 852cc FX1000: 999cc 824 EFI: 824cc
Cooling	Air cooled
Air Cleaner	Heavy duty canister
Engine Warranty	3 year

## DRIVE SYSTEM

Type	Dual hydrostatic
Pumps	21cc Hydro-Gear PY pumps
Wheel Motors	Parker TG310
Hydraulic Lines	Stainless steel Parker seal loc technology
Hydraulic Cooling	Oil cooler with 8" fan
Reservoir Capacity	3 gallons
Speed	Up to 14 mph
Parking Brakes	Patented automatic

## DECKS

Cutting Width	Side discharge: 54", 60", 66", 72" Rear discharge: 60", 72"
Cutting Heights	1" - 5.5"
Deck Lift	Foot operated
Depth	5.5"
Blades	3
Blade Length	54" deck: 3 - 18.5" x 2.5" x .20" 60" deck: 3 - 20.5" x 3.0" x .25" 66" deck: 3 - 22.5" x 3.0" x .25" 72" deck: 3 - 24.5" x 3.0" x .25"
Spindles	Ductile cast iron with steel shafts and sealed ball bearings
Deck Belts	1
Drive	Electric PTO clutch
Construction	7 ga. welded steel
Spindle Mounts	Reinforced 7 ga. spindle mount disc
Impact/Trim Areas	11 ga. formed channel w/ rolled edge

\* Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning and terrain.

\*\* Specifications are subject to change without notice.

## CONSTRUCTION

Frame	1.5" x 3.0" x .187" steel tubing
Front Caster Wheels	Mounted tapered wheel bearings and debris cap
Front Caster Forks	Fabricated 1/2" steel

## GENERAL

Seat	I3M suspension seat
Fuel Capacity	11.7 gallons
Cup Holder	Yes
Front Tire	13 x 6.5 - 6
Drive Tire	54" deck: 24 x 9.5 - 12 60", 66", 72" deck: 24 x 12 - 12

## DIMENSIONS

Weight	54": 1420 lbs    66": 1516 lbs 60": 1451 lbs    60"RD: 1566 lbs 72": 1526 lbs    72"RD: 1626 lbs
Height w/rops up	72.5"
Height w/rops Folded	46.8"
Length	54", 60" deck: 89", 60"RD deck: 91.5" 66" deck: 91.5" 72", 72"RD deck: 93"
Width	54" deck: 60"    66" deck: 72" 60" deck: 66"    72" deck: 78" 60"RD deck: 66"    72"RD deck: 73.23"
Tire Width	54", 60", 60"RD deck: 57" 66", 72", 72"RD deck: 60"

## PRODUCTIVITY\*

Acres Per Hour	54": 6.11    60": 6.78 66": 7.46    72": 8.14
----------------	--

## OPTIONAL ACCESSORIES

Steering extension kit	Flex Forks®
High vacuum deck kit	Mulch kit
Electric deck lift	Light kit
Rear hitch kit	Sand kit
Deck rear anti-scalp wheels	Stripe kit
BacVac bagger	Beacon kit
Semi pneumatic front tire	Flasher kit
3-bag powered bagger (12 bushels)	

## SUPER Z | AT A GLANCE

- VX4® deck - 7-gauge thick deck offering excellent performance in all conditions
- Heavy-duty fabricated frame – unmatched durability
- Exclusive SmoothTrak™ steering – responsive, precise control
- Up to 14 mph – gets the job done fast
- Unmatched hydraulics – oil shuttle, cooler separates it from the competition
- 13" front and 24" drive tires
- Top pinning height adjustment



Visit [hustlerturf.com](http://hustlerturf.com)  
and try our compare products tool!